

6015/PLE/8,6CUM, 4902818 TUBE AS

Standard Equipment:

POWERTRAIN

Cat C27 diesel engine
Air-to-Air After Cooling (ATAAC)
Automatic engine idle shut down
24-volt dual electric starters
Electronically controlled fan speed
Exhaust system heat shields
Heavy-duty air filters
Hydraulically driven radiator fan
Starting aid - automatic ether
Turbocharger, two
Two stage fuel filtration with water separator.

UNDERCARRIAGE

Fully hydraulic self-adjusting track tensioning system
HD tracks with cast double-grouser track pads
HD fixed axle rollers
HD fixed axle idlers
HD protection package
-Final drive hydraulic supply line guards
-Final drive motor and gearcase guards
-Slew bearing lube lines
Hydraulic retarder valve (automatic)
Positive Pin Retention (PPR)
sealed and greased track design.

HYDRAULICS

Power Management System with integrated controls
-Flow-on-demand management of implement travel and swing pumps
-Load Enhanced Anticipatory Control (LEAC)
-Proportional Priority Pressure Compensating (PPPC) technology
- Altitude Limit 1,000meters
Pressure cut-off for main pumps
Cooling of pump transmission gear oil
Closed loop swing circuit
Automatic swing holding brake
S.O.S Sampling Ports
Full-flow high-pressure filtration
Pressure filters, servo circuit
Swing charge filters
Pump case return screens
Boom float valves

ELECTRICAL

Four maintenance-free batteries
Lockable battery isolator switch
14 LED high-brightness working flood lights
5 LED service lights

Starting receptacle

Two electric horns

OPERATOR ENVIRONMENT

Single HVAC system

Pressurized cab with positive filtration

Heated cab mirror

Color LCD display with warning, filter/fluid change, and hour meter

Fully adjustable suspension seat

Height-adjustable joystick consoles

Adjustable armrest

Travel control pedals with removable hand levers

FM/AM radio with MP3 auxiliary port

SAFETY AND SECURITY

Acoustic travel alarm

Beacon

Handrail enclosed walkways and platforms

Neutral lever (lock out) for all controls

Operator Protective Guard (top guard)

Retractable seatbelt

Safety glass

OTHER STANDARD EQUIPMENT

Automatic lubrication system, (68L, 18 gal capacity)

Cat MineStar- Solutions Ready

Central ground-level service area

CONFIGURATION :

471-7359 6015B ME backhoe unit with C27 Engine (TIER 4)

535-8570 8,6 M3 BUCKET (535-8570)

0P-9003 LANE 3 ORDER

423-3583 SHORT STICK-3,4

506-8615 ME BACHOE BOOM (7.6M)

432-5357 RADIATOR, LRC

455-1870 TRACK, 700MM DG PPR2

438-1139 BREATHER

439-5511 LIGHTS, LED, 4200 LUMENS

441-8437 PROD LINK, SATELLITE PLE631

429-0560 NO WINDSHIELD GUARD

441-1055 LADDER, FIXED

440-2703 LINES, STANDARD WEATHER

442-7194 LUBRICATION, STANDARD

436-5963 GUARD,TRACK GUIDE, CENTER

442-9473 FILMS, ISO

0P-7534 PACKING, EXPORT CRATING